

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/10/2015 Reviewed on 07/10/2015

1 Identification

- · Product identifier
- · Trade name: Precision Calibration Gas Mixture
- · Product number: G-7315
- Relevant identified uses of the substance or mixture and uses advised against Used for calibration of gas measuring devices. Not suitable for human consumption.
- · Product description Calibration gas mixture consisting of Butadiene, Oxygen and Nitrogen.
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
 Gasco Affiliates, LLC
 320 Scarlett Blvd.
 Oldsmar, Fl 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920 E-MAIL: info@gascogas.com Emergency telephone number:

Inside the US: 1-800-424-9300 (CHEMTREC, 24 hours) Outside the US: 1-703-527-3887 (CHEMTREC, 24 hours)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS04

- · Signal word Warning
- · Hazard statements

Contains gas under pressure; may explode if heated.

· Precautionary statements

Protect from sunlight. Store in a well-ventilated place.

· Unknown acute toxicity:

100 percent of the mixture consists of ingredient(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 0 Reactivity = 0

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/10/2015 Reviewed on 07/10/2015

Trade name: Precision Calibration Gas Mixture

· HMIS-ratings (scale 0 - 4)



Hazard(s) not otherwise classified (HNOC): None known

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous Components:		
CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ♦ Press. Gas, H280; Simple Asphyxiant	78.999-81.9999%
CAS: 7782-44-7	Oxygen ♦ Oxid. Gas 1, H270; ♦ Press. Gas, H280	18-21%
CAS: 106-99-0 RTECS: EI 9275000	Butadiene The Flam. Gas 1, H220; Muta. 1B, H340; Carc. 1A, H350; Press. Gas, H280	0.0001-0.001%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Generally the product does not irritate with inhalation.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Generally the product does not irritate the skin.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

Wash with soap and water.

If skin irritation occurs, consult a doctor.

· After eye contact:

Not anticipated under normal use.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Not a normal route of entry.

If swallowed and symptoms occur, consult a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Use fire fighting measures that suit the environment.

Use water spray to cool fire-exposed containers.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/10/2015 Reviewed on 07/10/2015

Trade name: Precision Calibration Gas Mixture

· Special hazards arising from the substance or mixture

Closed containers may explode when exposed to extreme heat.

If incinerated, product will releaset the following toxic fumes: Oxides of Carbon and Nitrogen (NOx).

Advice for firefighters

This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.

· Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Treat any fumes as toxic.

Ensure adequate ventilation

Keep people at a distance and stay upwind.

In a confined area, NIOSH approved respiratory protection may be required.

- · Environmental precautions: Inform authorities in case of gas release.
- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not cut, grind or weld on container that contains or contained product.

Do not spray on a naked flame or any incandescent material.

· Conditions for safe storage, including any incompatibilities

Store away from strong oxidizing agents, phosphorous, organic materials and powdered metals.

- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/10/2015 Reviewed on 07/10/2015

Trade name: Precision Calibration Gas Mixture

· Control parameters

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

7727-37-9 Nitrogen

TLV withdrawn TLV, see App. F; simple asphyxiant

106-99-0 Butadiene

PEL Short-term value: 11 mg/m³, 5 ppm Long-term value: 2.21 mg/m³, 1 ppm

see 29 CFR 1910.1051; 29 CFR 1910.19(1)

REL See Pocket Guide App. A

TLV Long-term value: 4.4 mg/m³, 2 ppm

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Breathing equipment:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

- · Protection of hands: Not required.
- · Eye protection: Not necessary under normal conditions.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Color:
Gaseous
Clear, colorless
Odorless
Odor threshold:
Not determined.

· **pH-value:** Not determined.

Change in condition

Melting point/Melting range:
 Boiling point/Boiling range:
 Not determined.
 Not applicable.
 Flammability (solid, gaseous):
 Not determined.

Ignition temperature:

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not self-igniting.

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/10/2015 Reviewed on 07/10/2015

Trade name: Precision Calibration Gas Mixture

· Danger of explosion: Not determined.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

Vapor pressure: Not determined.

· Density:

Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Other information No further relevant information available.

10 Stability and reactivity

- · **Reactivity** No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · *Incompatible materials:* Strong oxidizing agents, phosphorous, organic materials and powdered metals.
- Hazardous decomposition products: Carbon Oxides and Nitrogen Oxides (NOx).

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
106-99-0 Butadiene			
Oral	LD50	5480 mg/kg (rat)	
Inhalative	LC50/4 h	285 mg/l (rat)	

- · Primary irritant effect:
- on the skin: No irritating effect.
- · on the eye: No irritating effect.
- · Additional toxicological information:
- · Carcinogenic categories
- IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

106-99-0 Butadiene

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 07/10/2015 Issue date 07/10/2015

Trade name: Precision Calibration Gas Mixture

· NTP (National Toxicology Program)	
106-99-0 Butadiene	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients are listed.	

2 Ecological information

- · *Toxicity* The hazards for the aquatic environment are unknown.
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

3 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty cylinder for recycling.

NOTE: Check with the local easte authority before placing any gas cylinder into waste container for pickup. GASCO encourages the consumer to return all cylinders.

UN1956

· Waste disposal kev:

The U.S. EPA has not published waste disposal numbers for this product's components.

- · Uncleaned packagings:
- · Recommendation: Return cylinder and unused product to supplier.

! Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA
- · UN proper shipping name
- · DOT
- · ADR
- · IMDG, IATA
- · Transport hazard class(es)
- · DOT



· Class 2.2

Compressed gas, n.o.s.

UN1956 Compressed gas, n.o.s. COMPRESSED GAS, N.O.S.

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/10/2015 Reviewed on 07/10/2015

Trade name: Precision Calibration Gas Mixture

· Label 2.2

· ADR



· Class 2.2 1A 2.2

· IMDG, IATA



• **Class** 2.2 • **Label** 2.2

· Packing group

· DOT, ADR, IMDG, IATA Non-Regulated Material

Environmental hazards: Not applicable. Special precautions for user Not applicable.

Danger code (Kemler):EMS Number:F-C,S-V

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations** On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

· ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN1956, Compressed gas, n.o.s., 2.2

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

106-99-0 Butadiene

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/10/2015 Reviewed on 07/10/2015

Trade name: Precision Calibration Gas Mixture

 TSCA (Toxic Substances Con 	trol Act):
--	------------

All ingredients are listed.

· California Proposition 65

· Chemicals known to cause cancer:

106-99-0 Butadiene

· Chemicals known to cause reproductive toxicity for females:

106-99-0 Butadiene

· Chemicals known to cause reproductive toxicity for males:

106-99-0 Butadiene

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

106-99-0 Butadiene CaH

TLV (Threshold Limit Value established by ACGIH)

106-99-0 Butadiene A2

· NIOSH-Ca (National Institute for Occupational Safety and Health)

106-99-0 Butadiene

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS04

· Signal word Warning

· Hazard statements

Contains gas under pressure; may explode if heated.

Precautionary statements

Protect from sunlight. Store in a well-ventilated place.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

	State Right to Know		
ľ	CAS: 7727-37-9	Nitrogen	78.999-81.9999%
	RTECS: QW 9700000	Press. Gas, H280; Simple Asphyxiant	
	CAS: 7782-44-7	Oxygen	18-21%
		♦ Oxid. Gas 1, H270; ♦ Press. Gas, H280	
	CAS: 106-99-0	Butadiene	0.0001-0.001%
	RTECS: EI 9275000	Flam. Gas 1, H220; S Muta. 1B, H340; Carc. 1A, H350; Press. Gas, H280	
ľ	All ingredients are liste	d.	

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 07/10/2015 Issue date 07/10/2015

Trade name: Precision Calibration Gas Mixture

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Other information

· Relevant phrases

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affilitates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

Date of preparation / last revision 07/10/2015 / -

Abbreviations and acronvms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases, Hazard Category 1

Oxid. Gas 1: Oxidising Gases, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Muta. 1B: Germ cell mutagenicity, Hazard Category 1B

Carc. 1A: Carcinogenicity, Hazard Category 1A

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106