

## Non-Shock Lanyard

Part #	Size	Description
01280	4' - 6'	Adjustable Non-Shock Absorbing Lanyard
01250	2'	Non-Shock Absorbing Lanyard - Single Leg
01255	3'	Non-Shock Absorbing Lanyard - Single Leg
01260	4'	Non-Shock Absorbing Lanyard - Single Leg
01265	6'	Non-Shock Absorbing Lanyard - Single Leg
01251	3'	Non-Shock Absorbing Lanyard - Single Leg w/Rebar Hook
01261	4'	Non-Shock Absorbing Lanyard - Single Leg w/Rebar Hook
01265	6'	Non-Shock Absorbing Lanyard - Single Leg w/Rebar Hook
01270	4' - 6'	Non-Shock Absorbing Lanyard - Double Leg
01271	4' - 6'	Non-Shock Absorbing Lanyard - Double Leg w/Rebar Hooks
01289	6'	Non-Shock Absorbing Lanyard - w/Adjustable D-ring & Rebar Hooks
01121	18"	Extension Lanyard w/Snap Hook End
01122	18"	Extension Lanyard w/Web Loop End



Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Non-Shock Lanyards are suitable for the following applications:



**Personal Fall Arrest:** Non-Shock Lanyard may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Non-Shock Absorbing Lanyards may only be used in Fall Arrest applications when used with compatible shock absorber extension.



**Restraint:** Non-Shock Lanyard may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



**Work Positioning:** Non-Shock Lanyard may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.



**Rescue/Confined Space:** Non-Shock Lanyard may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, Shoulder.

**For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.**



Not all Guardian Non-Shock Absorbing Lanyards may be used in every application type. ALWAYS consider lanyard length, design, and any other structural components. ALWAYS read and adhere to product labeling. A Competent Person MUST make a determination regarding correct lanyard application and compatibility.

Materials: polyester, nylon, steel, aluminum. Contact Guardian Fall Protection with any questions regarding specific lanyard components or composition.

MAXIMUM 1 user per Non-Shock Lanyard.