

## BULL RING ANCHOR

ANCHORAGE CONNECTOR

### FEATURES & BENEFITS

- Can be used in a wide variety of applications
- Lightweight and durable
- Compatible with horizontal lifelines
- Easy to Install
- Fasteners Included
- Reusable



#### PIVOTING BULL RING

Allows anchor to be loaded from both sides

#### HOLE PATTERNS

Accomodate 6 nails or 5 screws

SHOWN:  
**PART #00484**

# SPECIFICATIONS

## STANDARDS:

OSHA 1926 Subpart M & 1910  
ANSI Z359.18-17\* & A10.32-12

*\*For certain applications.  
See instructions for more detail.*

Type A Anchorage Connector

## WORKER CAPACITY:

130-420 lbs.

## PERFORMANCE:

- Maximum Users: 1
- 5,000 lb. MBS (Minimum Breaking Strength)

## NOTES:

- Minimum service temperature: -30°F
- Wood substrate only, 3.5" combined thickness when installed with nails.
- All fasteners must be fully embedded in substrate.

## MATERIALS:

Galvanized steel or stainless steel

PART #	DESCRIPTION	WEIGHT
00484	Galvanized Steel Bull Ring Anchor	2.25 Lbs
00484-SS	Stainless Steel Bull Ring Anchor	2.25 Lbs

# APPLICATIONS



## PERSONAL FALL ARREST:

Bull Ring Anchors may be used in Personal Fall Arrest applications to support:

- MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs.
- Maximum free fall is 6'.
- Applicable D-rings: Dorsal



## WORK POSITIONING:

Bull Ring Anchors, configured with side or shoulder D-rings, may be used in Work Positioning applications.

- Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands.
- Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs.
- Maximum allowable free fall is 2'.
- Applicable D-rings: Side & Shoulder.



## RESTRAINT:

Bull Ring Anchors may be used in Restraint applications. Restraint systems:

- Prevent workers from reaching the leading edge of a fall hazard.
- Always account for fully deployed length of lanyard / SRL.
- Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
- No free fall is permitted.
- Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal).
- Applicable D-rings: Dorsal, Chest, Side, Shoulder.



**NEED MORE INFORMATION?**

P: 1.800.466.6385 | VISIT OUR WEBSITE: [GUARDIANFALL.COM](http://GUARDIANFALL.COM)