

HALO ANCHOR

ANCHORAGE CONNECTOR

FEATURES & BENEFITS

- Lightweight and durable
- Fits roof pitches from $\frac{0}{12}$ - $\frac{12}{12}$
- Easy to Install
- Fasteners Included



SHOWN:
PART #00482

SPECIFICATIONS

STANDARDS:

OSHA 1926 Subpart M & 1910
ANSI Z359.18-17 & A10.32-12
Type A Anchorage Connector

MATERIALS:

Forged Steel, Zinc-plated Steel,
& Rubber

WORKER CAPACITY:

130-420 lbs.

PERFORMANCE:

- Maximum Users: 1
- 5,000 lb. MBS
(Minimum Breaking Strength)

NOTES:

- Minimum service temperature: -30°F
- Min. substrate thickness requirements:
Wood: 3/4" CDX or better.
Metal: 20 gauge or better.
- Fasteners:
Wood: (6) 1/4" x 3" lag screws or (12) 16d nails.
Metal: (6) 1/4" x 3" metal deck screws.
- All fasteners must be fully embedded in substrate.

PART #	DESCRIPTION	WEIGHT
00482	Halo Anchor	6 Lbs

PRODUCT COMPLIANCE	OSHA 1910 & OSHA 1926 SUBPART M	ANSI Z359.18 & ANSI A10.32
Wood Installations (Except Screws in Truss)	Yes	No
Wood Installations, Screws in Truss	Yes	Yes
Metal Installations	Yes	No

APPLICATIONS



PERSONAL FALL ARREST:

- Halo Anchors may be used in Personal Fall Arrest applications to support:
- Maximum 1 Personal Fall Arrest System (PFAS).
 - Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs.
 - Maximum free fall is 6' or up to 12' if used in combination with equipment explicitly certified for such use.
 - Applicable D-rings: Dorsal



WORK POSITIONING:

- Halo Anchors may be used in Work Positioning applications.
- Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands.
 - Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs.
 - Maximum allowable free fall is 2'.
 - Applicable D-rings: Side.



RESTRAINT:

- Halo Anchors may be used in Restraint applications. Restraint systems:
- Prevent workers from reaching the leading edge of a fall hazard.
 - Always account for fully deployed length of lanyard/SRL.
 - Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
 - No free fall is permitted.
 - May only be used on surfaces with slopes up to 4/12 (vertical/horizontal)
 - Applicable D-rings: Dorsal, Chest, Side, & Shoulder.



NEED MORE INFORMATION?

P: 1.800.466.6385 | VISIT OUR WEBSITE: GUARDIANFALL.COM