

PITCH PRO

ANCHORAGE CONNECTOR

TECHNICAL DATA & SELL SHEET - ISSUE 1



TESTED IN Z359.7/ISO 17025
COMPLIANT LAB

CONNECTION POINT

Easy & secure connecting point.

**IDEAL FOR
SLOPED ROOF,
ASPHALT SHINGLE
CONSTRUCTION**

EASY TO INSTALL

Installs quickly with
nails or screws.

FASTENER HOLES

Offset holes are
easy on trusses.

POWDER-COATED STEEL

For superior durability

LIGHTWEIGHT & DURABLE



Material: Powder-coated Steel

Capacity: 130-420 Lbs.

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**

PITCH PRO

ANCHORAGE CONNECTOR

TECHNICAL DATA & SELL SHEET - ISSUE 1

Standards

- OSHA 1910
- OSHA 1926 Subpart M
- ANSI Z359.18-2017
- ANSI A10.32-2012



Performance:

- Minimum Breaking Strength (MBS): 5,000 lbs.
- Maximum Users: 1
- Roof Pitch: 0/12 - Vertical/Sheer
- Minimum Service Temperature: -30°F

Notes:

- Ok for use in horizontal lifeline (HLL) applications, however must only be used with #30800 Big Boss Horizontal Lifeline and for a maximum of two workers only

Applications



Personal Fall Arrest: Pitch Pro may be used in Personal Fall Arrest applications as a component of a Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



Restraint: Pitch Pro may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, & Shoulder.



Work Positioning: Pitch Pro may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side.



Rescue/Confined Space: Pitch Pro may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, & Shoulder.

PITCH PRO

ANCHORAGE CONNECTOR

TECHNICAL DATA & SELL SHEET - ISSUE 1

Prod. Code	Description	User Weight
10540	Steel Pitch Pro - Single Pk - Black	130-420 lbs
10541	Steel Pitch Pro - Single Pk - Brown	130-420 lbs
10542	Steel Pitch Pro - Single Pk - Grey	130-420 lbs
10543	Steel Pitch Pro - 25 Pk - Black	130-420 lbs
10544	Steel Pitch Pro - 25 Pk - Brown	130-420 lbs
10545	Steel Pitch Pro - 25 Pk - Grey	130-420 lbs

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**